



TIPO	Ø A	Ø B	Ø C	Ø D	E	F	G	H	I	L	M	N	O
120	1500	800	300	400	2700	1200	300	1300	750	150	600	350	300
220	2000	1000	300	400	2900	1300	300	1300	1000	250	500	400	400
350	2500	1000	300	400	3050	1300	400	1350	1000	250	500	400	500
520	3000	1500	400	400	3700	1800	450	1450	1050	250	500	400	600
750	3500	1500	400	400	4450	2300	600	1550	1150	250	500	500	700
1150	4200	1500	400	550	4900	2300	900	1700	1300	300	500	600	800
1600	5000	1500	400	550	5650	2800	1000	1850	1650	300	500	750	1000
2000	6000	1500	400	550	6050	2800	1300	1950	1900	300	500	1100	1500

Diametro Bacino Ø	PORTATA Lt/sec		PORTATA m ³ /h		VOLUME m ³		POTENZA MOTORE Kw	TUBO ESTR. DN	TUBO Aria Ø	TUBO Acq. Ø	VELOCITA' ROTAZIONE PALE g/1'
	Liv. 1	Liv. 2	Liv. 1	Liv. 2	Liv. 1	Liv. 2					
1500	40	70	140	250	1,66	1,85	0,26	80	1" 1/4	1" 1/4	12
2000	65	120	235	430	2,2	3	0,26	80	1" 1/4	1" 1/4	17
2500	110	210	400	760	3,9	5,2	0,37	80	1" 1/4	1" 1/4	19
3000	190	340	680	1220	6,7	8,5	0,37	80	1" 1/4	1" 1/4	22
3500	300	520	1080	1870	10,5	13	0,75	80	1" 1/4	1" 1/4	25
4200	520	880	1870	3160	18	22	1,1	100	1" 1/2	1" 1/4	27
5000	850	1400	3050	5000	30	35	1,5	100	1" 1/2	1" 1/4	31
6000	1400	2300	5000	8300	50	58	2,2	100	1" 1/2	1" 1/2	47

6600 l/m.

 FRIULANACOSTRUZIONI				33074 Vigonovo di Fontanafredda (Pordenone) Italia Zona Industriale "La Croce" Tel. 0434/999606 - Fax 998637			
cliente				prodotto			
				ASSIEME DI DIMENSIONAMENTO DISSABBIATORE PISTA			
disegnato				data			
dis. <i>Z. M.</i>				contr. appr. data			
				D B 1 3 1 0			
				A B C D E F G H			